

# CONDENSERS



## DESCRIPTION OF STANDARD UNIT:

- 2hp, 2.5hp, 3hp & 3.5hp available in 1-phase & 3-phase
- COPELAND scroll compressors
- Noise reducing compressor jacket
- Crankcase heater included
- Fan speed controller – regulated on pressure
- Auto/Auto low & high pressure switch
- Super Energy Efficient - High COP's
- Filter Drier
- Drier sight glass
- Liquid receiver
- Pre-wired for pump down operation
- Easy Access to all components for servicing
- No Rotalock Valves to minimise refrigerant leakage
- Pressure tested to 300psi before despatch
- CE Marked
- Refrigerant gas - R404/R407/R134

MODEL		ALZB15-1P	ALZB19-1P	ALZB21-1P	ALZB26-1P	ALZB30-3P	ALZB38-3P	ALZB45-3P	
Width	mm	936							
Depth		355							
Height		835				1330			
Qty of Fans		1			2				
Nominal Hp		2	2.5	3	3.5	4	5	6	
Connections		5/8 + 3/8				3/8 + 3/4			
Voltage		220-240v/1hp/50Hz or 3-phase					380-420v/3hp/50Hz		
Run Current	A	12.8		16.4	18	10.3	12.8	13.1	
Start Current	A	58	61	82	97	49	65.5	74	
Oil Charge	Ltrs	1.3	1.24			1.89			
Noise level	dBa	34	35	38	39	40	41	42	
Weight	Kgs	68	70	71	88	97	98	104	
Duty @ -10 evap. 32 ambient		3600	4450	5200	5850	7200	8450	9550	

