



DESCRIPTION OF STANDARD UNIT:

- Construction of stainless steel
- Side and front glasses: double with silver serigraphy
- 3 rows of adjustable shelves
- Highlighted shelves LED
- Epos ticket strips
- Forced cooling
- Temperature range: 0 - +6°C;
Heated model: +40°C - +90°C
- Automatic defrosting
- Automatic water evaporation
- Access to condenser from the front

OPTIONS:

- For external condensing unit - cooling power demand: 800 W/1m at evaporating temp. -10°C

Type: C-1 GN	Length (mm)	Depth (mm)	Height (mm)	Useful Capacity	Weight	Daily Consumption kWh	Electrical Input Power W
GN 60/CH/O/FT, GN 60/CH/Z/FT	600	750	1395	0.8	TBC	13.7/9.0	1400/100
GN 90/CH/O/FT, GN 90/CH/Z/FT	900			1.3		14.5/10.5	1500/1100
GN 120/CH/O/FT, GN 120/CH/Z/FT	1200			1.8		16.5/13.0	1650/1300
GN 60/GR/Z/FT	600			0.8		6.5	1700
GN 90/GR/Z/FT	900			1.3		9.5	2100
GN 120/GR/Z/FT	1200			1.8		12.5	3300
GN 60/NE/Z/FT	600			0.8		0.6	100
GN 90/NE/Z/FT	900			1.3		0.8	150
GN 120/NE/Z/FT	1200			1.8		1.0	200

* Values are provided for an evaporation temp. of -10°C, condensation temp. of +45°C, ambient temp of +25°C and relative humidity of 60%.
CH- Refrigerated GR- Heated NE- Ambient O- Self-service (open front) Z- Assisted-service (closed front)

