

VARNA - OPEN FRONTED

DESCRIPTION OF STANDARD UNIT:

- Double glazed end walls
- 5 rows of adjustable shelves
- T5 Canopy lighting
- Night blind
- Temperature range: +2 - +8°C
- Automatic condensate evaporation

OPTIONS:

- Glass sliding doors (DP) (except VR and MVR 60 and 110)
 - Highlighted shelves
 - Hooks for meat
 - Plexiglas or wired shelf stoppers
 - Wheels
 - Multiplexing
- For external condensing unit (AZ) – cooling power demand: 1500 W/1mr at evaporating temp. -10°C



TYPE R-1 MVR / VR	Length with sides* (mm)	Depth (mm)	Height (mm)	Useful surface (m ²)	Weight (kg)	Daily consumption (kWh/24h)
60	600	620/780	2000±30	1,1/1,4	110/120	9,0/11,0
110	1100			1,9/2,9	180/190	13,0/14,5
130	1300			2,3/3,5	200/220	14,0/15,5
160	1600			2,9/4,4	230/250	15,0/16,5
190	1900			3,5/5,2	250/270	21,0/22,5
210	2100			3,8/5,8	265/290	23,0/24,5
250	2500			4,4/7,0	300/320	38,0/39,0

TYPE: R-1 MVR / VR with doors	Quantity of DP* (pcs.)	Weight (kg)	Daily consumption (kWh/24h)
130	2	300/310	9,8/10,5
160	2	330/340	10,5/11,5
190	2	340/350	14,7/15,7
210	4	370/390	16,0/17,1
250	4	400/420	26,5/27,0

*DP – Sliding doors

**Only available on models 1.3m to 2.5m

