



DESCRIPTION OF STANDARD UNIT:

- Construction of stainless steel
- Side and front (closed version) glasses: double with silver serigraphy
- Perforated, stainless steel back panel in self-service version
- Highlighted, glass shelves or stainless steel shelves (hot version)
- Temperature range: +4 +10°C / +40 +90°C (hot version)
- Automatic water evaporation

OPTIONS:

- Wood casing
- Ultrasonic humidifier (in version with front glass)
- Self-service version with hanging doors on the back (DU)
- For external condensing unit – cooling power demand:
for closed version: 850 W/M at evaporating temp. -10°C
for self-service version: 1000 W/M at evaporating temp. -10°C
- Refrigerated corners

TYPE C-1 VN	Length (mm)	Depth (mm)	Height (mm)	Useful surface (m ²)	Weight (kg)	Daily consumption (kWh/24h)
60/CH/O, 60/CH/Z	600	800	1360±35	1,0	110/140	10,5/8,0
90/CH/O, 90/CH/Z	900			1,5	140/170	13,0/10,0
120/CH/O, 120/CH/Z	1200			2,0	180/210	15,5/13,5
60/GR	600			1,0	90	6,5
90/GR	900			1,5	120	9,5
120/GR	1200			2,0	150	12,5
NW/45/CH, NZ/45/CH	1150			1,1/0,9	130	14,5

CH – refrigerated, GR – hot
O – self-service, Z – closed

