



## DESCRIPTION OF STANDARD UNIT:

- ABS sides
- Front made of powder – coated steel
- Chrome bumper
- Stainless steel worktop
- Storage chamber made of steel with the antimicrobial coating SANISTIL
- Forced (W) or gravity (G) cooling
- Temperature range: 0 ÷ +6°C (forced cooling) / +2 ÷ +8°C (gravity cooling)

## OPTIONS:

- Lift up system of front glass (TL)
- Stainless steel storage chamber
- Automatic condensate evaporation
- Self-service version (OT): temperature range: +4 ÷ +10°C
- For external condensing unit (AZ) – cooling power demand: 400 W/1mr at evaporating temp. -15°C (forced cooling); 350W/1mr at evaporating temp. -15°C (gravity cooling)
- Refrigerated corners (ventilated, CAUTION! Lack of version with lift up system of front glass)



# HAVANA

TYPE L-1 HW/G	Length with sides* (mm)	Depth (mm)	Height (mm)	Useful surface (m <sup>2</sup> )	Weight (kg)	Daily consumption (kWh/24h)
100/110	1080	1150	1250±30	0,75	100	4,0
125/110	1330			0,9	120	5,54
150/110	1580			1,1	150	5,56
200/110	2080			1,5	190	7,23
250/110	2580			1,85	220	10,68
300/110	3080			2,2	250	10,69
375/110	3830			2,8	390	13,08

G – gravity cooling \* Side 40 mm

TYPE L-1 HW/W	Length with sides* (mm)	Depth (mm)	Height (mm)	Useful surface (m <sup>2</sup> )	Weight (kg)	Daily consumption (kWh/24h)
100/110	1080	1150	1250±30	0,85	100	4,39
125/110	1330			1,05	120	6,02
150/110	1580			1,3	150	8,4
200/110	2080			1,7	190	11,33
250/110	2580			2,12	220	11,11
300/110	3080			2,55	250	14,0
375/110	3830			3,2	390	15,0
NZ/90, NW/90	1550x1550			1,2	140	–

W – forced cooling \* Side 40 mm

TYPE L-1 HW/W OT	Length with sides* (mm)	Depth (mm)	Height (mm)	Useful surface (m <sup>2</sup> )	Weight (kg)	Daily consumption (kWh/24h)
100/110	1080	1150	900±30	0,85	90	4,39
125/110	1330			1,05	105	6,02
150/110	1580			1,3	135	8,04
200/110	2080			1,7	170	11,33
250/110	2580			2,12	200	13,11
300/110	3080			2,55	225	12,25
375/110	3830			3,2	360	15,0

W – forced cooling OT – self-service \* Side 40 mm



