

# TOFINO

## DESCRIPTION OF STANDARD UNIT:

- Integral condensing unit
- Construction of powder-coated steel
- ABS Sides
- Front made of powder-coated steel
- Front and side glasses with silver serigraphy
- Stainless steel worktop
- White lighting LED
- Plexiglas night curtain
- Space for additional ice-cream containers (under exhibition)
- Wheels
- Digital controller
- Gravity cooling
- Temperature range: °12 ÷ -22°C (for maximum ambient temperature of +30°C and relative humidity 60%)
- Automatic defrosting
- Automatic condensate evaporation
- Refrigerating factor: R404A
- Voltage: ~230V/50Hz

## OPTIONS:

- Highlighted Plexiglas front
- MDF sides
- Containers
- Spoon washer
- For external condensing unit (AZ): cooling power demand: 450W/1mr at evaporating temp. -35°C



TYPE K-1 TF	Length (mm)	Depth (mm)	Height (mm)	Containers quantity (pcs.)	Weight (kg)	Daily consumption** (kWh/24h)
7	995	910	1250	7	140	8,2
9	1250			9	160	10,6
10	1325			10	180	11,2
11	1490			11	190	11,7
13	1655			13	200	12,0

\* for containers 165×360×120 (h) mm – 5,2 l

\*\* Values provided for an evaporation temperature of -35°C and condensation temperature of +45°C



